INT-SF-B

PARTITION KEYPAD

The **INT–SF–B** partition keypad allows you to control operation of each alarm system based on the control panels of **INTEGRA** and **INTEGRA Plus** families. To maintain a uniform design line of the controls, it is recommended that the INT–SF partition keypad be used in alarm systems including the **INT–KLFR**, **INT–TSI**, **INT–TSG2**, **INT–TSH2** and **INT–KSG** keypads.

- white color backlight
- controls single partition in the system
- PANIC, FIRE and AUX alarms triggered from keypad
- LEDs for partition status indication
- buzzer for acoustic signaling of selected system events
- access control functions
- relay for electromagnetic lock / electric strike control
- door status monitoring input
- available in white (**INT–SF–W**), black (**INT–SF–B**), light with silver frame (**INT–SF–SSW**), dark with silver frame (**INT–SF–BSB**) and white with silver frame (**INT–SF–WSW**)

TECHNICAL DATA

Supply voltage	12 V DC
Operating temperature range	-10°C...+55°C
Standby mode current consumption	20 mA
Max. current consumption	40 mA
Weight	180 g
Maximum humidity	93±3%
Dimensions	80 x 143 x 25 mm
Environmental class according to EN50130-5	II
Relay output (resistive load)	1 A / 30 V DC

The actual appearance of the products may differ from the presented images. Product descriptions are provided in the web service for information purposes only.