

DG-1 LPG

LIQUIFIED PETROLEUM GAS DETECTOR

DG-1 LPG is a microprocessor-based detector of LPG (propane-butane) gas, which is used e.g. as fuel in vehicles. It is, therefore, recommended that you install it in such spaces as garages, underground car parks, etc. Also, premises where heating equipment, cookers or burners running on this gas is installed, are exposed to propane-butane leaks. Due to the nature of LPG, which is heavier than air, the detector should be installed just above the floor in the supervised room. The digital algorithm of gas detection and the function of temperature compensation ensure correct operation over a wide range of ambient temperatures as well as immunity to false alarms. The device detects dangerous propane-butane concentrations in the room, i.e. above the 20% threshold level of the so-called lower explosive limit (10% for pre-alarm), and triggers alarm. The DG-1 LPG detector is designed for use as part of an alarm system. The self-diagnostic function is constantly monitoring the gas sensor for supply voltage status as well as correct performance, which ensures reliable operation of the detector.

- digital signal analysis
- optical and acoustical indication of threshold concentration detection
- low current consumption
- full autodiagnosics
- pre-alarm feature
- green LED indicator



TECHNICAL DATA

Operating temperature range	-10...+55 °C
Standby mode current consumption	35 mA
Max. current consumption	45 mA
Weight	62 g
Dimensions	ø 97 x 36 mm



The actual appearance of the products may differ from the presented images. Product descriptions are provided in the web service for information purposes only.